FEATURES

600mm Adjustable Height by One-Click

The electric stand is built-in with drive motor, supports wire and wireless remote control.
Adjustable height is at 600mm, and the center height of screen ranges from 1088mm to 1680mm.
The design of one-click lifting , is very smooth, stable and silent during lifting, offering excellent use experience.

Safe Load Capacity 80kgs

The lifting structure is made of matt aluminum in stable and durable, lifting smoothly.

Supports wireless

Supports wireless and bluetooth remote control ranging in 5 meters, stable and reliable.

Free and Soundless Movement

The base is made of SPCC steel, solid and durable.
It is equipped with four medical universal adjustable casters for easy, stable and soundless movement.
Each caster combines with brake independently for fixed parking.

Hidden Cable Routing

The motor is applied with spiral spring cable which is efficient and durable without twisting.
The stand body adopts hidden cable routing for safe and neat.

Eye-catched Apperance & Wide Application

The whole stand is made of industrial grade materials, solid and durable.
The textured black and white appearance is fashion and simple. Combined with 55"-65" HD large screen, it brilliantly becomes the focus of visual.
The modern electric lifting stand, is operated in the way of intelligent control, more efficient and reliable.
It is widely used in enterprises, hotels, shopping malls, TV stations, schools, exhibition halls etc.

APPLICATIONS

SPECIFICATIONS

Enclosure			
Model No.	SF-2013E	Compatible Screens	55"-65"
Material	SPCC+Aluminum (the lifting stand)	VESA	900x600mm (max)
Surface Finishing	Powder coating+ Anodizing (the lifting stand)	Net Weight	65.5kg
Bearing Capacity	80kg, the maximum eccentricity is 25cm.	Speed	11mm/s
Overall Size	1195x752x1682.5 mm (the center height of bracket)		
Lifting Height	Adjustable height is at 60cm, and the center height of screen ranges from 1088mm to 1680mm.		
Power			
Voltage	100-240VAC, 50/60HZ	Motor Power	120W (max)
Devices			
Remote Control	Wire/Wireless remote control (option)		
Application			
Working Temperature	0~40℃	Storage Temperature	-20~60℃
Working Humidity	20%~80%	Storage Humidity	10%~90%
Application	Indoor		
Warm Tips			
1. The maximum continuous working time of the motor shall not exceed 2 minutes. 2. Movement shall be after taking a break for at least 30 minutes. 3. Movement: please move by pushing the stand but not the bracket or screen etc.			

XIAMEN MAKEN TECH CO., LTD.
Web: www.maken.com