DUAL-SCREEN VERTICAL ORDERING KIOSK

KH-2720 / KH-3220

1080P HD Commercial Display Screen
10-point Capacitive Touch
Option: 27" Screen/32" Screen

FEATURES

Front-rear Dual Screen For Double Efficiency

The kiosk body is state-of-the-art metal configuration adopted, for vertical flooring application, slim figure with strong stable base to keep safe in public and small in occupation.

The kiosk has of front-rear dual screens, highly improves the commercial running efficiency and also space occupation; it is very suitable for catering industry like fast food restaurant, snack bar, coffee bar etc.

Perfect Visual & Lightning Touch

The kiosk is allocated with high-brand HD 1080P commercial display screen, offering 178° viewing and exquisite image, bringing you excellent visual enjoyment.

Adopted with powerful central motherboard supports 7x24 hours running, stable and durable 10 point capacitive touch, immediate response, and sentitive to kinds of gestures by point or slide touch with nice usage experience.

Internal Modularization

Display screen is configurated with side lockable door for easy daily maintenance and printing paper change.

Interal electronic devices are individually located with metal mounting bracket, for non-interference working environment and safety, and also easy maintenance and replacement.

Bilateral Speaker Enhance Marketing Effect

The kiosk is equipped with speakers on two sides, and supports more than 30 media broadcast modes,offering fabulous using experience and improving brand image of the store

Hidden Power Routing

Two options for cable routing

Option 1: In the location of the kiosk where there is plug, just make the reserved outlet in the base align to the plug, then inserts the cable into the plug. No power cord is exposed.

Option 2: Should location without plug, the cable goes through inner and extends to side of the stand from the bottom, to reduce the cable exposed. That makes the application space safe and neat.

APPLICATIONS





SPECIFICATIONS



Product name		32" Dual-screen Vertical Ordering Kiosk		27" Dual-screen Vertical Ordering Kiosk	
OS hardware	Operating System	WIN 10 (for service only)	Android 9.1	WIN 10 (for service only)	Android 9.1
	CPU	Intel Celeron J4115 quad-core 2.5 GHz	RK3288 Cortex-A35 quad-core 2.3 GHz	Intel Celeron J4115 quad-core 2.5 GHz	RK3288 Cortex-A35 quad-core 2.3 GHz
	System Memory	4G/8G	2G/4G	4G/8G	2G/4G
	Disk	128G/256G/512G	16G/32G	128G/256G/512G	16G/32G
	Speaker	3W*2	3W*2	3W*2	3W*2
	Interface	USB*4/LAN*1	USB*3/LAN*1	USB*4/LAN*1	USB*3/LAN*1
	Network	Ethernet/WFI	Ethernet/WFI	Ethernet/WFI	Ethernet/WFI
Touch Screen	Type	PCAP 10 points		PCAP 10 points	
	Response Time	10ms		10ms	
LCD	Type	TFT-LCD		TFT-LCD	
	Contrast Ratio	1000:1	3000:1	3000:1	
	Brightness	400cd/m²		300cd/m²	
	Response Time	8ms		13ms	
	Max Resolution	1920*1080		1920*1080	
	Viewing Angle	H:178° V:178°		H:178° V:178°	
	Aspect Ratio	16:9		16:9	
	Display Colors	16.7M		16.7M	
	Refresh Rate	60Hz		60Hz	
	Panel life	30000 hours		30000 hours	
Built-in Devices	Printer	80mm thermal printer with auto cutter		80mm thermal printer with auto cutter	
	Scanner	2D Area Imaging scanner		2D Area Imaging scanner	
	Camera	2 million pixels(prime lens,1920*1080@30fps		2 million pixels(prime lens,1920*1080@30fps	
	Card Reader	Customer purchase		Customer purchase	
Power	Voltage	100-240VAC, 50/60HZ		100-240VAC, 50/60HZ	
	Power Consumption	<240W		<220W	
Enclosure	Material	SPCC		SPCC	
	Surface	Powder coaxing		Powder coaxing	
	Colour	Black or customized		Black or customized	
	Overall Dimension	520x400x1940		520x400x1644	
	Package(mm)	2200x510x400		1910x520x400	
	Net Weight	115.7kg		98.7kg	
	Gross Weight	135.3kg		116.7kg	
Application	Application	Indoor		Indoor	
	Working Temperature	0~40℃		0~40℃	
	Storage Temperature	-20~60℃		-20~60℃	
	Working Humidity	20%~80%		20%~80%	
	Storage Humidity	10%~90%		10%~90%	

ASSEMBLY & INSTALLATION

Packing List

Installation

Placement options

Floor installation



Arrange the cable



Product structure

Change the paper roll